

# Pulling eye

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

The **Pulling Eye** is designed to provide a functional and safe way of tensioning down guys at the anchor location. It provides a working load of 3,000 lbs with a 5:1 ratio safety factor (Ultimate strength of 15,000 lbs).

## Features

- Facilitates safe, fast installation of all dead-ends by a pulling point at the anchor
- Installs around the anchor hardware in seconds
- Nodular Iron housing and keeper with EHS steel bolt and nut
- Corrosion resistant powder coating iron
- Accommodates anchor rods from 1/2" - 1-1/4" (12.7 - 31.75 mm)
- Reusable
- Lightweight

## Documentation

### Application Procedures

[SP-2013 \(Pulling Eye\)](#)

## Catalog Pages

[Pulling Eye Catalogue](#)

## Sales Materials

[Pulling Eye - Sell Sheet](#)

## Part Tables

<b>Catalog Number</b>	<b>Description</b>	<b>Std. Ctn.</b>
PE-0300	Pulling Eye	4 Units

## Replacement Parts

<b>Catalog Number</b>	<b>Description</b>	<b>Std. Ctn.</b>
PE-A-0002	Pulling Eye: Keeper	As Required
PE-B-2019	Pulling Eye: Bolt	As Required
PE-C-0607	Pulling Eye: Nut	As Required

Note: 3,000 lb. working load is based on a 5 to 1 safety factor.