



ARMADILLO® Selection Guide

Just follow these simple steps:

STEP ONE

Use this table to select the size of our ARMADILLO Stainless required based on the pair count.

ARMADILLO Stainless Capacities	
Pair Count of Cables	ARMADILLO Stainless Size (mm)
50 thru 300	4" x 25" (102 x 635)
300 thru 600	6.5" x 22" (165 x 559)
300 thru 1100	6.5" x 28" (165 x 711)
900 thru 1500	6.5" x 38" (165 x 965)
900 thru 2100	8" x 28" (203 x 711)
1200 thru 2400	8" x 38" (203 x 965)
1500 thru 2700	8" x 45" (203 x 1143)
1500 thru 2700	9.5" x 28" (241 x 711)
1800 thru 3600	9.5" x 38" (241 x 965)
2100 thru 4200	9.5" x 45" (241 x 1143)
2100 thru 4200	9.5" x 53" *(241 x 1356)
2400 thru 3000	12.5" x 28" (318 x 711)
2700 thru 3600	12.5" x 38" (318 x 965)
3000 thru 4200	12.5" x 45" (318 x 1143)
3000 thru 4800	12.5" x 65" *(318 x 1651)

NOTE: Capacities based on 24 gauge wire and industry standard splice modules.

*Shells are welded

STEP TWO

Choose from one of the ARMADILLO Stainless Kits with drilled end plates or the ARMADILLO Stainless Filling Flange Kits with drilled end plates.

These are the original PREFORMED™ Splice Case Kits and PREFORMED Splice Case with Filling Flange Kits that you are familiar with.

STEP THREE

Select and order the individual components you need.

All components are interchangeable. You can have a closure with a Sealing Washer End Plate on one end and a Drilled End Plate on the other.

C-Cement

Used to prepare cable for LOCK-TAPE™ Sealant in ARMADILLO Drillable End Plates.

C-Cement is required to install in an ARMADILLO Splice Case.

Catalog Number	Description
80802377	4 oz. Can C-Cement
80805238	1 oz. Tube C-Cement