





Bird Flight Diverter



APPROX. $\varnothing 90$

GENERAL RECOMMENDATIONS

The Bird Flight Diverter is designed to make overhead lines visible to birds and provides an economic means of reducing the hazard to both lines and birds. For low and medium voltage construction (up to 40 kV) it is applied to the phase conductors (bare or jacketed). For high voltages it is used on the earth wire.

The fitting is light in weight, offers little wind resistance and is easily and quickly applied by hand or by hot sticks. The positive grip of the fitting on the conductor ensures that it remains in the applied position and cannot move along the span under vibration.

Visibility: The diverter section increases the visibility profile of the cable or conductor to a degree necessary to ensure safety, but avoids an undesirably bulky outline.

ENSURE THE CORRECT SIZE

FITTING IS USED. For detailed method of installation refer to application instructions. Hot stick application is fast and simple with standard equipment.

Spacing: Spacing distances are not critical and will depend upon local conditions. Since wind resistance is very limited, sufficient fittings can be used to ensure adequate visibility without creating stresses on the line. When marking adjacent spans, overall visibility is improved by staggering the application.

Manufactured from rigid solid high impact polyvinyl chloride, possessing excellent chemical and strength properties and which will retain good physical characteristics within the range of extreme temperatures. Outdoor aging tests indicate that the material does not deteriorate in function or appearance from the effects of severe weather conditions. Industrial fumes and salt water cannot seriously degrade the properties of rigid PVC.

Black, grey or white.

Bird Flight Diverters are supplied right hand lay for both right hand and left hand lay bare conductors and insulated cables.

The Double Loop design is shown overleaf.

CATALOGUE NO.	CONDUCTOR DIAMETER
	RANGE (mm)
BFD 249 – 349P/*	6.3 – 8.9
BFD 350 – 449P/*	9.0 – 11.4
BFD 450 – 599P/*	11.5 – 15.2
BFD 600 – 749P/*	15.3 – 19.0

Add suffix B, W or G for colour Black, White or Grey respectively

Approx. weight: 70 grams