

# Aerial Cable Attachment Hardware Solutions

FIBERLIGN® Series ADSS & Lashing Messenger Cable Storage Systems

## FIBERLIGN® In-Span Storage



12" and 16" Bracket Sizes

### QUICK Installation



Captures cable loop

Slides into final position

The innovative Cable Capture Tabs of the FIBERLIGN® In-Span Storage (FIS) are designed to make aerial slack cable storage faster and easier. During installation, the cable is clipped into the tabs and then the storage bracket is pulled into its final position at the back of the cable loop.


The cable is secure and the installer's hands are free to apply cable ties.

Less cable ties are required, saving time and money.


Adjustments to the cable loop or storage bracket are simple.

### Key Features:

- Available with hanger brackets for either lashed messenger cable systems or ADSS
- Vertical stacking of multiple cables provides large storage capacity in a small profile
- Abrasion Protectors or Uni-Group Cable Guide are offered as pole pass options for cable slack against the pole
- Uni-Group Cable Guide guides cable through low profile applications between communication and utility zones



ADSS Installation



Messenger Installation

### Pole Pass Options



Abrasion Protectors



Uni-Group Cable Guide

FIS for Lashed Messenger Cables			
Catalog No.	Storage Bracket Size (cm)	Maximum Fiber Cable Diameter (cm)	Description
FIS12M	12" (30.5)	0.60" (1.5 cm)	Pair of 12" (30.5 cm) diameter storage brackets with messenger hanger brackets
FIS16M	16" (40.6)	0.80" (2.0 cm)	Pair of 16" (40.6 cm) diameter storage brackets with messenger hanger brackets

FIS for ADSS Cables			
Catalog No.	Storage Bracket Size (cm)	Maximum Fiber Cable Diameter (cm)	Description
FIS12A	12" (30.5)	0.60" (1.5 cm)	Pair of 12" (30.5 cm) diameter storage brackets with ADSS hanger brackets
FIS16A	16" (40.6)	0.80" (2.0 cm)	Pair of 16" (40.6 cm) diameter storage brackets with ADSS hanger brackets

Ordering Instructions and Optional Accessories			
FISxxx-TU			
<b>Storage Bracket Loop Diameter</b>			
12 or 16	<b>xx</b>		
<b>Application</b>			
ADSS	<b>A</b>		
Messenger	<b>M</b>		
<b>Cable Ties</b>			
25 Pack of Cable Ties	<b>T</b>		
No Cable Ties	<b>Blank</b>		
<b>Pole Pass Option</b>			
Uni-Group Cable Guide	<b>U</b>		
Abrasion Protectors	<b>A</b>		
None	<b>Blank</b>		
Sample Catalog Number FIS16A -TU Pair of 16" (40.6 cm) diameter storage brackets for ADSS, 25 cable ties, and Uni-Group Cable Guide			