



FIBERLIGN® Suspension Unit only and not assembly

CATALOGUE NO. SUFFIX FAG	DIAMETER RANGE		STRUCTURAL REINFORCEMENT RODS			OUTER RODS		
	MIN. (mm)	MAX. (mm)	LENGTH (mm)	ROD DIA. (mm)	ROD PER SET	LENGTH (mm)	ROD DIAM. (mm)	ROD PER SET
354/381	8.9	9.7	1676	3.66	9	1372	5.18	11
382/398	9.7	10.1	1676	3.66	9	1372	5.18	11
399/418	10.1	10.6	1676	3.66	10	1372	5.18	11
419/439	10.6	11.2	1702	3.66	10	1397	5.18	11
440/458	11.2	11.6	1727	3.66	11	1422	5.18	11
477/503	12.1	12.8	1829	4.06	10	1524	6.35	10
512/536	13.0	13.6	1829	4.06	1	1549	6.35	10
537/559	13.6	14.2	1829	3.66	11	1524	6.35	10
566/573	14.4	14.6	1854	3.66	12	1549	6.35	10
574/598	14.6	15.2	1930	4.06	11	1626	6.35	11
599/625	15.2	15.9	1956	4.06	11	1651	6.35	11
626/666	15.9	16.9	1956	4.06	11	1651	6.35	11
667/710	16.9	18.0	2007	4.62	11	1676	6.35	12
729/750	18.5	19.0	2007	4.62	11	1702	6.35	12
751/786	19.1	20.0	2057	4.62	11	1727	6.35	12
787/814	20.0	20.7	2057	4.62	11	1753	6.35	12
908/916	23.1	23.3	2388	5.18	11	2083	7.62	11